


## Pressure Transmitter

### PX-25H Series



High Resolution



Narrow total error band



Excellent long-term Stability

## Description

The PX-25H series is a high performance configurable solution for pressure measurement. The micromachined silicon technology and analogue circuitry enables excellent accuracy and stability. On board temperature measurement provides real time temperature compensation while high resolution analogue signal path is available with fast response.

### Pressure Ranges (FRO) - Gauge

100 mbar to 150 bar (any zero based range between)  
Bi-directional from  $\pm 100$  mbar

### Pressure Ranges (FRO) - Absolute

250 mbar to 150 bar (any zero based range between)

### Overpressure

200% to 400% depending on pressure range (FRO)

### Output Signal (2-wire)

4 to 20 mA

### Load Impedance

> 5 kOhm

### Measurement Performance

Valid for Pressure Ranges  $\geq 1$  bar

### Accuracy

(includes non-linearity, hysteresis and repeatability)

Standard  $\leq \pm 0.1$  % FRO

optional  $\leq \pm 0.05$  % FRO

optional  $\leq \pm 0.02$  % FRO

### Total Error Band within Operating Temperature Range

(includes non-linearity, hysteresis, repeatability, zero and span settings, thermal shift on zero and span)

Standard  $\leq \pm 1$  % FRO

optional  $\leq \pm 0.5$  % FRO

optional  $\leq \pm 0.25$  % FRO

**Stability**  $\leq 0.1$  % FRO per year (typically)

**Response Time** < 0.5 ms

### Zero and Span Setting

Digital adjustable, optional

### Operating Temperature Range

-20°C to +80°C

### Compensation Temperature Range

-20°C to +80°C

### Supply Voltage (Vs)

9 to 32 VDC

### Material of Wetted Parts

1.4404 and 1.4435

### Electrical Connection

Cable length 1 m (IP67)

Plug EN 175301-803 Form A (IP65)

(DIN 43650) Mating Connector included

Plug M12x1, Mating Connector optional

### Pressure Connection

G1/4 female

G1/4 male, DIN 3852 T11, seal included

Others on Request

### Protection Rate

Depending on mating connector

### Weight

85 g, app.

### EMC

12 V/m 80 MHz-2 GHz to DIN EN 61326 (A)

### Vibration

DIN EN 60068-2-64 Grade 1

## Electrical Connections

Output	Function	M12x1	DIN 43650	Cable
mA	+ Vs	1	1	Brown
	- Vs	3	2	White
	Cable Screen			Black

## Dimensions (mm)

Dimension	C	B (Male)	B (Female)
M12x1	9.5	51.3	61.3
DIN 43650	28	53.6	63.6
Cable	11	48.5	58.5

Dimension	A	D
G1/4 male	12	$\varnothing 25$
G1/4 female	n.a.	$\varnothing 25$

